

# LINEAR 5 MK II 110 XA

## THE ALL-PURPOSE WORKHORSE

### Extremely compact and lightweight multifunctional mid/high unit

Part number: 1007959

The LINEAR 5 MK II 110 XA is a compact, flexible multifunctional mid/high unit with 10" woofer and tweeter with 1.4" voice coil. With its multifunctional enclosure shape with slanted monitor edge and a rotatable horn with a dispersion pattern of 80° x 60°, it covers an enormously wide range of system configurations. Its space-saving dimensions and narrow, horizontal dispersion allow low feedback, directional monitoring, even on small stages – even without turning the horn.

In addition to crystal-clear, assertive sound and impressive range, the LINEAR 5 MK II 110 XA features a remote-controllable high-performance DSP with integrated, directly selectable presets and DSP Out, which can route the processed signal from the speaker to a non-networked speaker, as well as a wide range of accessories.

The sturdy birch multiplex hybrid enclosure makes the LINEAR 5 MK II 110 XA a strong partner for bands and sound technicians – either as a transverse stage monitor or as a

powerful system mid/high unit together with the LINEAR 5 MK II subwoofers.

### Features

- Compact, multifunctional enclosure shape with 31° monitor slope
- 1200 W peak power bi-amped Class-D power amplifier
- Rotatable horn with 80° x 60° dispersion pattern
- Lockable, balanced XLR/TRS Combo input, balanced XLR output for analogue looping to an additional speaker
- Remote-controllable high-performance DSP with integrated directly selectable presets for the most common applications: Flat, Monitor, Low Cut, Remote
- Extensive DSP tools: fully parametric 10-band EQ with variable filter characteristics, High-Pass Filter, Low-Pass Filter, Polarity, Level, Delay, Limiter, Mute
- Professional, lockable EtherCon connector for connection to a Mac or PC to control the system
- DSP Out: balanced XLR output that transmits the processed signal from the speaker to a non-network-compatible speaker. The audio signal applied here can be extensively modified using the DSP CONTROL software
- HK AUDIO DuoTilt with 3° or 7° inclination
- Three reinforced M8 (AP-8) mounting points
- Lockable V-Lock mains cable
- Made in Germany



# LINEAR 5 MK II 110 XA



## Technical data

### LINEAR 5 MK II 110 XA

Max. SPL @ 10 % THD	127 dB half space (70 Hz - 12 kHz averaged)
Max. SPL Peak @ 10 % THD	135 dB half space*
Frequency response +/-3 dB	74 Hz - 12 kHz
Frequency response -10 dB	68 Hz - 19 kHz
Power amp output (RMS/Peak)	600 / 1,200 W
Amplifier type	Class D - bi-amped
Woofers	-
Low/mid speaker	1 x 10", 2" voice coil
HF driver	1", 1.4" voice coil
Horn characteristics	80° x 60° CD horn, rotatable
Active x-over frequency	2.1 kHz FIR X-over with 72 dB/oct.
Maximum input level	20 dBu
Analogue inputs	1 x XLR combo balanced
Analogue Thru	1 x XLR balanced
DSP Out	1 x XLR balanced
Network port	EtherCON RJ45, 1 x In
Filter presets	Flat, Monitor, Low Cut, Remote
Remote software	DSP CONTROL (Windows, macOS)
DSP functions	Fully parametric 10-band EQ with variable filter characteristics, High-Pass Filter, Low-Pass Filter, Polarity, Level, Delay, Limiter, Mute
Sample rate	48 kHz
System latency	Less than 2 ms
Mains connection	1x IEC connector with V-Lock securing system, 100-240 V
Power consumption	1 A / 100-240 V nominal according to EN 62368-1
Set-up angle (Monitor mode)	31°
Pole mount	DuoTilt 3°/7°
Rigging points	3x M8 (AP-8)
Carrying handles	1 x SingleGrip
Housing	Hybrid (birch multiplex/MDF)
Surface	Black acrylic enamel
Front grille	2 mm metal grille backed with black acoustic foam
Dimensions (WxHxD)	36 x 52.5 x 30 cm 14-1/16 x 20-43/64 x 11-13/16"
Weight	14.9 kg / 32.85 lbs



## Optional accessories



### LINEAR 5 MK II Weather Protective Cover 110 XA

Part number: 1008044

Made to measure and equipped with many practical details, the Weather Protective Covers are the perfect protection against moisture and humidity, and at the same time a sturdy transport cover for all LINEAR 5 MK II mid/high units and subwoofers.

Behind the front flap, a waterproof acoustic gauze protects the front of the speakers and the drivers without affecting the systems' sound. The front flap can be simply and securely rolled up at the head end without interfering with stacking or clustering.

On the rear, sturdy, transparent viewing windows keep water away from the electronics, but ensure the settings can be read at all times and provide access to the controls as well as a cable entry.

The handles can still be used thanks to sealable recesses or notches. Sufficient ventilation of the electronics is ensured at all times.

- Tough rain and transport protection with easy handling
- Controls can be read and accessed at all times through transparent viewing windows
- Mounting poles can be used and installed with the protective cover in place
- Sturdy and discreet design
- Custom-fit covers are available for all LINEAR 5 MK II series units

## Accessories for rigging and mounting



### AP-8 attachment point

Part number: 1007538

With a high load capacity of up to 360 kg (WLL), or 180 kg within the scope of BGV-C1, the AP-8 Attachment Point allows for the safe installation of speaker cabinets with M8 rigging points on steel cables or chains.

### Tilt-Unit

Part number: 1007972

The Tilt Unit allows the mid/high units to be tilted directly on the subwoofer without a mounting pole. Like a mounting pole, the Tilt Unit is screwed directly into the M20 mount of the LINEAR 5 MK II SUB. This means that the DuoTilt can also be used at tilt angles of both  $-3^\circ$  and  $-7^\circ$  in a stack setup, and the Tilt-Unit prevents the mid/high units from slipping.





# LINEAR 5 MK II 110 XA

